



The *TRI Ultraviolet Series* is an effective way to provide safe, bacteria-free, water for your home or office 24 hours a day 7 days a week. The TRI Ultraviolet Disinfection Systems are setting the standards for water disinfection requirements in the industry.

FEATURES:

- Standard Warranty
- Touchscreen Visual & Audible Alarms
- 30 Day Replacement Alarm & Countdown Timer
- Lamp Life Expired Alarm
- UV Lamp Out Alarm
- UV Intensity Low Output Alarm
- 365 Day Resettable Lamp Life Counter
- Flow Control
- Solenoid Valve Connection



BENEFITS:

- No taste or odor
- Eliminates microbiological contaminants without chemicals
- Bacteria, viruses and other organisms are destroyed safely inside a factory sealed and tested stainless steel chamber.



LED Control Box

Screen Shots



SPECIFICATIONS:



Model#	Max. Flow GPM	No. Lamps	KW @ 120V	AMP @ 120V	Pipe Size	Overall Dimensions L x W x D	Wetted Material	Shipping Weight
TRI - 8	8	1	0.03	0.25	3/4" FNPT / 1" MNPT	21" x 3.5" x 3.5"	304 SS	9 lbs.
TRI- 12	12	1	0.03	0.25	3/4" FNPT / 1" MNPT	32" x 3.5" x 3.5"	304 SS	18 lbs.
TRI - 20	20	1	0.03	0.25	3/4" FNPT / 1" MNPT	35" x 5" x 5"	304 SS	21 lbs.

NOTES: 220V Specs are available upon request

TRI Series UV DISINFECTION

Parts Breakdown:

1. Mounting Bracket
2. Outlet
3. Site Port
4. Quartz Sleeve
5. UV Lamp
6. Inlet
7. Quartz Sleeve Stabilizer
8. Optional Bottom Mounting Bracket



OPTIONAL ACCESSORIES



Solenoid:

This solenoid acts as a fail safe shut-off valve. Providing extra protection for the system.



UV Probe:

UV dosage metering device. This UV Probe reads only the 254-nm intensity output of the Ultraviolet Light within the UV treatment chamber. Optional on PFC units only.